



SEE MORE. DO MORE.



ZEBRA® ZD500™ PRINTER SPECIFICATIONS



Specifications are provided for reference and are based on printer tests using Genuine Zebra™ supplies. Results may vary in actual application settings or when using other than recommended Zebra supplies. Zebra recommends always qualifying any application with thorough testing.

Standard Features

Printer Features

- Thermal transfer or direct thermal print methods
- ZPL® programming language
- Dual-wall frame construction
- Tool-less printhead and platen replacement
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Simplified calibration of media
- Quad connectivity: USB, Parallel, Serial, and Ethernet
- 128 MB Std SDRAM memory (4 MB available to user)
- 256 MB Std Flash memory (56 MB available to user)
- Real-time clock
- LCD user interface
- Zebra E³™ Printhead Energy Control
- ENERGY STAR® qualified
- Link-OS®-enabled
- Print Touch™ app
- Unicode compliant for multi-language printing
- 16 resident expandable ZPL II® bitmap fonts
- Two resident scalable ZPL fonts
- Auto-switching 100-240V power supply
- Multi-position gap and moveable black-line media sensors
- Head-up sensor
- Standard tear-off mode feature
- Programmable print speeds of 2, 3, 4, 5 & 6 ips (51, 76, 102, 127 & 152 mm/s)
- 3" media core adaptor
- Zebra printer driver for Windows®

Firmware

- ZPL II – Universal language for Zebra printers. Simplifies label formatting and enables format compatibility with existing systems that run Zebra printers.
- XML-enabled Printing — allows XML communications for barcode label printing' capability.
- Web View – Connect and control Zebra bar code printers via the printer's Web interface using a common Web browser.
- Alert – Printers equipped with ZebraNet® print servers will notify you via any email-enabled, wired, or wireless device to minimize downtime.

Optional Features

- 300 dpi print resolution (12 dots/mm)
- Wireless – 802.11 a/b/g/n and Bluetooth® 3.0
- UHF RFID printer/encoder (factory installed)
- Dispenser (peeler) – Label peel and present with present sensor
- Cutter:
 - Continuous paper, lined label and tag stock
 - Maximum thickness 0.010" (0.254 mm)
- Font Packs – Asian and other international font kits
- Power Cord – US, Europe, UK, Australia, Japan and Taiwan
- ZBI 2.0™ – Field installed via activation key

Accessories

- ZKDU™ – Keyboard display unit for ZPL and EPL™
- KDU Plus™ – Full-size keyboard with LCD for stand-alone printing applications



SEE MORE. DO MORE.



Link-OS Solutions

Software Tools

- Document Design: Quickly design a customized print solution using your business data and Zebra's intuitive, plug-and-print design tools
- Printer Integration: Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems
- Printer Management: Manage your print operations locally and globally with Zebra's suite of device management tools
- Developer Tools: Provides you with the tools you need to create your own apps, including documentation, source code, programming languages, templates and more
- Zebra Setup Utility: Single printer configuration utility
- Zebra Universal Driver: The most powerful driver available from Zebra for Windows 95/98/2000/2003/ME/NT/XP
- ZebraDesigner™ Driver: Zebra driver compliant with Windows 95/98/2000/2003/ME/NT/XP, and Vista™ (downloadable from www.Zebra.com)

Communication and Interface Capabilities

- RS-232 auto-sensing Serial interface, DB-9
- USB V2.0, bi-directional
- Centronics® Parallel 36 pin
- Ethernet – 10/100 internal
- Wireless – 802.11 a/b/g/n and Bluetooth 3.0

Printing Specifications

| Resolution | 203 dots/inch (dpi) (8 dots/mm) | 300 dots/inch (dpi) (12 dots/mm) |
|-------------------------------------|--|--|
| Speed inch/sec - ips (mm/sec) | Programmable 2, 3, 4, 5 with 6 max. (51, 76, 102, 127 with max.152) | Programmable 2, 3 with 4 max. (51, 76, with max.102) |
| Dot pitch | 0.0049" (0.13 mm) | 0.0033" (0.08 mm) |
| Max. print length | 39.0" (991 mm) | 39.0" (991 mm) |
| Min. print length | One dot | One dot |
| Max. print width | 4.09" (104 mm) | 4.09" (104 mm) |
| Min. print width | One dot | One dot |
| Barcode modulus "X" Dimension | 5 mil to 50 mil | 3.27 mil to 32.67 mil |

Ribbon Specifications (Thermal Transfer Units)

NOTE: For optimum print quality and printer performance, use of Genuine Zebra ribbon is recommended as well as a notched ribbon core

- Ribbon Width: 1.33" (33.8 mm) to 4.3" (109 mm)
- Ribbon Capacity: 1 roll of ribbon per 1 roll of 5" OD media
- Core ID: 0.5" (12.7 mm)
- Ribbon OD: 1.36" (35 mm)
- Ribbon Length: 244' (74 m) using 0.000328" ribbon thickness
- Ribbon Type: wax, wax/resin and resin

Media Specifications

NOTE: For optimum print quality and printer performance, use of Genuine Zebra supplies is recommended.

- Media Width: 0.75" (19 mm) - 4.25" (108 mm)
- Label Length:
 - Minimum using tear-off mode: .25" (6.3 mm)
 - Minimum with label present sensor used - 0.50" (12.7 mm)
 - Minimum with cutter - 1.0" (25.4 mm)
- Core Inner Diameter: 0.5"/12.7 mm, 1.0"/25 mm, 1.375"/35 mm, 1.5"/37.1 mm, 3"/76 mm
- Maximum Roll Diameter: 5.00" (127 mm)
- Media Thickness: 0.003" (0.08 mm) - 0.012" (0.305 mm)
- Media Sensing: fixed reflective and multiposition transmissive gap, moveable black line and notch
- Media Types: Roll-fed or fan-fold, die-cut or continuous direct thermal labels with or without black mark, tag stock, continuous receipt paper and wristbands
- Dispenser peeler may not work with all media types and should be tested for media compatibility.

Calibration Procedure

- A manual calibration procedure can also be performed, if required. Consult your "User's Guide" for more details on the specific manual calibration steps.



SEE MORE. DO MORE.



ZPL Programming Language (ZPL/ZPL II)

- Communicates in printable ASCII characters
- Compatible with mainframe, mini and PC hosts
- Downloadable objects include graphics and bitmap fonts, label templates and formats
- Automatic memory allocation for format while printing
- Automatic serialization of fields
- Format inversion (white on black)
- Mirror-image printing
- Four position field rotation (0°, 90°, 180°, 270°)
- Slew command
- Programmable label quantities with print, pause
- Status messages to host upon request

ZPL Font Specifications 203 dpi (8 dots/mm)

| Font | Matrix (in dots) (H x W) | Type* | Minimum Char. Size (H x W) | Maximum C.P.I. |
|------|--------------------------|--------|---|----------------|
| A | 9 x 5 | U-L-D | .044" x .030" | 33.3 |
| B | 11 x 7 | U | .054" x .044" | 22.7 |
| C,D | 18 x 10 | U-L-D | .089" x .059" | 16.9 |
| E | 28 x 15 | OCR-B | .138" x .098" | 10.2 |
| F | 26 x 13 | U-L-D | .128" x .079" | 12.7 |
| G | 60 x 40 | U-L-D | .295" x .236" | 4.2 |
| H | 21 x 13 | OCR-A | .103" x .093" | 10.8 |
| GS | 24 x 24 | SYMBOL | .118" x .118" | 8.5 |
| P-V | | U-L-D | Backward compatible w/ S-300 Scalable (Smooth) Font | |
| Ø | 15 x 12 | U-L-D | | |

ZPL Font Specifications 300 dpi (12 dots/mm)

| Font | Matrix (in dots) (H x W) | Type* | Minimum Char. Size (H x W) | Maximum C.P.I. |
|------|--------------------------|--------|----------------------------|----------------|
| A | 9 x 5 | U-L-D | .030" x .020" | 50.8 |
| B | 11 x 7 | U | .037" x .030" | 33.8 |
| C,D | 18 x 10 | U-L-D | .060" x .040" | 25.4 |
| E | 41 x 20 | OCR-B | .138" x .085" | 11.5 |
| F | 26 x 13 | U-L-D | .085" x .053" | 19.06 |
| G | 60 x 40 | U-L-D | .200" x .160" | 6.36 |
| H | 30 x 19 | OCR-A | .100" x .098" | 10.02 |
| GS | 24 x 24 | SYMBOL | .80" x .80" | 12.7 |
| P-V | | U-L-D | Scalable (Smooth) Font | |
| Ø | 15 x 12 | U-L-D | | |

*U = upper case, L = lower case, D = descenders

- Character Fonts: Standard bitmapped Zebra fonts: A, B, C, D, E (OCR-B), F, G, H, (OCR-A), GS, P, Q, R, S,

- T, U, V & Ø Smooth font (CG Triumvirate™ Bold Condensed)
- Supports user-defined fonts and graphics – including custom logos
- Bitmap fonts are expandable up to 10 times, height and width independent. Fonts E and H (OCR-B and OCR-A), however, are not considered in spec when expanded.
- Smooth scalable font Ø (CG Triumvirate Bold Condensed*) is expandable dot-by-dot, height and width independent, while maintaining edges to a max. 1500 x 1500 dots
- Swiss 721 font

*Contains UFST® from Agfa Monotype Corporation

ZPL Barcode Symbologies

- Barcode Ratios: 2:1 (non-rotated) and 3:1
- Linear Barcodes: Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPC-A and UPC-E with EAN 2- or 5-digit extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar and GS1 DataBar (formerly RSS)
- 2-Dimensional: PDF417, MicroPDF417, Code 49, Maxicode, Codablock, Data Matrix, QR code, Aztec



SEE MORE. DO MORE.



Electrical Specifications

- Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz, rated at 100 Watts
- ENERGY STAR qualified

Agency Approvals

- Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN55022
- Class-B, EN61000-3-2, EN61000-3-0 and EN55024, CCC, Wi-Fi®-certified
- Safety: IEC 60950-1:2005 + A1:2009, EN 60950-1:2006 + A11:2009 + A12:2011 + A1:2010 +AC:2011, UL 60950-1:2007 R12.11, CAN/CSA-C22.2 No. 60950-1-07 + A1:2011 and TUV NRTL

Environmental Specifications

- Operating Temperature: 40° to 105°F (4.4° to 41°C)
- Storage Temperature: -40° to 140°F (-40° to 60°C)
- Operating Humidity: 10% to 90% non-condensing R.H.
- Storage Humidity: 5% to 95% non-condensing R.H.

Preventative Maintenance

- Zebra recommends cleaning the printer on a regular basis using standard Zebra printer parts and cleaning supplies. Consult your “User’s Guide” for further details.

Physical Specifications *(no options installed)*

| | ZD500 |
|--------|------------------|
| Height | 7.5" (191 mm) |
| Width | 7.6" (193 mm) |
| Depth | 10.0" (254 mm) |
| Weight | 4.6 lbs (2.1 kg) |



Corporate Headquarters
 +1 800 423 0442
 inquiry4@zebra.com

Asia-Pacific Headquarters
 +65 6858 0722
 apacchannelmarketing@zebra.com

EMEA Headquarters
 +44 (0)1628 556000
 mseurope@zebra.com

Latin America Headquarters
 +1 847 955 2283
 inquiry4@zebra.com

Other Locations / USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

©2014 ZIH Corp. Link-OS, Zebra, the Zebra head graphic, ZebraNet and ZPL are trademarks of ZIH Corp, registered in many jurisdictions worldwide. ENERGY STAR is a registered mark owned by the U.S. government. All rights reserved. All other trademarks are the property of their respective owners.